

SLIDING DOOR

The Classic Range





CARINYA CLEARLY BETTER

The Caringa Classic Sliding Door is a unique combination of form and function not previously available in the residential category.

Besides a modern designer look, the Carinya Classic Sliding Door is packed with a multitude of performance features, many of which are simply not available in competing products.

Rather than unsightly exposed tracks found in most residential doors, Carinya has a complete range of threshold and jamb infills as well as end caps to conceal all cavities. This not only provides a superior quality, commercial grade finish but also minimises places for insects, dirt and grit to gather.

An internally concealed weather flap also reduces air and water infilt ation and minimises insect intrusion through the drain holes.

All Carinya sliding doors feature a choice of sill configuations catering for every weather performance requirement, including a wheelchair accessible sill.

There is also a range of attractive interlock options to meet a wide variety of wind load requirements up to the most demanding cyclonic conditions.

The entire Carinya Collection has been fully tested to meet or exceed Australian Standards AS2047, AS1170:2011, AS1191:2002 and AS3959:2009.

Why Carinya is better

- ✓ Commercial design pedigree.
- ✓ Superior Designer look created by Architects and Design Engineers.
- ✓ Suitable for all glazing sizes from 4mm through to 10.5mm.
- ✓ Suitable for double glazing up to 18mm insulated glass units.
- ✓ Commercial grade 5 pin locking system in a range of colours.
- ✓ Unique roller system rated up to 160kgs per door panel.
- ✓ Tracks covered for that complete, up-market designer look.
- ✓ Infills, end caps and weather flaps guard against air, water, grit and insect penetration.
- ✓ Fully tested and certified for cyclonic regions C & D.
- ✓ Fully tested and certified to bushfire conditions up to BAL40.
- ✓ Fully tested and certified to high Acoustic requirements.
- ✓ The only residential sliding door designed by a market leader in commercial doors and windows.



The Carinya Classic Sliding Door has been matched with commercially designed hardware to ensure style and durability.



Functional and stylish Yarra Curve door lock (shown above). Yarra Edge door lock with optional stylish colours available.



ALSPEC's high performance, commercial door roller used in the Carinya residential sliding door for smooth operation.

Carinya windows and doors: Commercially-bred. Clearly better.



The Yarra Curve door lock provides functionality and varying finish options for your project. This functional design allows for ease of use and utilises 5 pin cylinder security for peace of mind.

Custom bump stops and end caps have been designed to minimise door slamming, and add to the aesthetic appeal of a professionally finished product, creating a door of unique quality in the residential market.

To maximise the performance of your sliding door we have utilised a proprietary ALSPEC roller system. It's the same system used throughout the commercial range and is available in two gauges - General use: for the majority of loads up to 80kg per panel; and Heavy duty commercial: designed for extra large sashes and major double glazing loads up to 160kg per panel.

Both roller systems have been designed to integrate with the stiles to create a strong and robust panel, minimising movement in joints and opportunities for air infilt ation.



Our Carinya Dealers are pleased to offer a solution for multiple keys for your doors and windows. It is possible to have 1 key for your front door, sliding door, french door, bi-fold door, sliding window, awning winder, double hung window and security door.

With Carinya's Master Key there's less keys... and less fuss!

Applications

- · New residential construction.
- · Door replacement and renovation.
- · Aged care & wheelchair requirements.
- · Low-rise multi unit developments.
- · Suitable for cyclonic regions C & D.

Specifications

- · Maximum Panel Height: 2400mm
- · Maximum Panel Width: 1200mm
- · Maximum Single Glazed Thickness: 10.5mm
- · Maximum Double Glazed Thickness: 18mm
- Maximum Sash Weight: 160kg
 *subject to site conditions

Options

- A range of sill options available for increased structural, water performance and design flexibility.
- A range of interlocks complete with end caps for varying wind load requirements.
- $\boldsymbol{\cdot}$ Choice of configu ations available, including stacking and corner options.
- · A range of mid rails available for semi-commercial unit developments.

Configurations

Your Carinya Dealer can offer the typical standard configurations below, as well as custom options to suit your requirements:

















Experience the Carinya Collection www.carinyawindows.com.au











